UNI-PRINTER MODEL UP 400-P

STANDARD FEATURES AND SPECIFICATIONS

Vertical pad motion eliminates pad vibration and resultant delays

Greater work-space area

Rigid frame ensures smooth operation

Modular design enables in-line use

All controls are conveniently located for fast set-up

Programmable

controller Single

auto-mixing cycle

Variable speed

Cycle and pad delay Double print control X-Y-

R pad adjustment Pad stroke adjustment in pick-

up and printing positions

X-Y inkwell and plate adjustment

Self-adjusting doctor blade Quick-

change doctor blade and flood bar

Quick-change inkwell and plate

Digital counter

Emergency stop

Transparent side guards

Cycle Capacity - up to 1400 cycles/hour

Drive - electro-pneumatic

Air Supply -80 psi

Air Consumption -7 cu. ft. /min.

Input Voltage - 115 volts - 50/60 Hz

Weight - 530 lbs.

INKWELL OPTIONS

Inkwell 4" x 6"

Inkwell 4" x 8"

Inkwell 4" x 10"

Doctor Blade Assembly 5"

Doctor Blade Assembly 7"

Doctor Blade Assembly 9"

MACHINE OPTIONS

Foot Switch

X-Y Table 6" x 8"

X-Y Table 9" x 12"

Rotary Table - Electric Drive

PAINT

Chemical Resistant Special Colors, add

Reprinted by AFM Engineering, Inc. 1313 E. Borchard Ave. Santa Ana, CA 92705 Phone: 714.547.0194 Fax: 714.542.2728 Email info@afmeng.com Web Site afmeng.com