

UNI-PRINTER MODEL UP 800

STANDARD FEATURES AND SPECIFICATIONS

Greater work-space area
Rigid frame ensures smooth operation
Modular design enables in-line use
All controls are conveniently located for fast set-up
Programmable controller Single auto-mixing cycle Variable speed
Cycle and pad delay Double print control X-Y-R pad adjustment
Pad stroke adjustment in pick-up and printing positions
X-Y Inkwell and plate adjustment
Self-adjusting doctor blade Quick-change doctor blade and flood bar
Quick-change inkwell and plate
Digital counter
Emergency stop
Transparent side guards
Cycle Capacity - up to 600 cycles/hour
Drive - electro-pneumatic
Air Supply -85 psi
Air Consumption -10 cu.ft./min.
Input Voltage - 115 volts-50/60 Hz
Weight - 1250 lbs.

INKWELL OPTIONS

Inkwell 7" x 12"
Inkwell 7" x 14"
Inkwell 7" x 16"
Inkwell 7" x 18"
Inkwell 7" x 20"
Inkwell 8" x 12"
Inkwell 8" x 14"
Inkwell 8" x 16"
Inkwell 8" x 18"
Doctor Blade Assembly 11"
Doctor Blade Assembly 13"
Doctor Blade Assembly 15"
Doctor Blade Assembly 17"
Doctor Blade Assembly 19"

MACHINE OPTIONS

Foot Switch
X-Y Table 9" x 12"
Rotary Table - Electric Drive
Rotary Table - Electric Drive

PAINT

Chemical Resistant
Special Colors, Add